

# ANY-WEIGH® Bench Scales

## Applications

### PROCESS WEIGHING

- Check Weighing
- Hand Ads
- Filling
- Laboratory
- Force



## Features

### C2® Electronic Calibration

- Electronic calibration without test weights



### ANY-WEIGH® Standard Features

- Stainless Steel
- Solid Construction
- Low Profile

### Universal

- C2 Electronic Calibration

### Analog

- Built-in 4-20mA Communications
- Pre-Calibrated

### DeviceNet

- Built-in DeviceNet Communications
- Pre-Calibrated
- WAVERSAVER®
- C2 Electronic Calibration
- THE BUTTON One Touch Calibration

The ANY-WEIGH® Bench scales provide complete flexibility in size and capacity for use in a wide range of weighing applications. With their rugged construction and stainless steel tops, ANY-WEIGH Scales are a great fit for both laboratory and industrial installations.

The ANY-WEIGH line of bench scales can be configured with standard interfacing to a weight instrument or with a built-in, direct connection to a PLC, PAC, DCS or PC.

### C2® ELECTRONIC CALIBRATION

With a push of a button in a Hardy Controller, C2 enables a fast, accurate, electronic calibration without test weights. The C2 system reduces downtime for installation or repairs and eliminates test weight related injuries.

### UNIVERSAL SCALE (HI SBU Series)

Directly attach the scale's 15-foot cable to any weighing instrument or controller. If interfacing with a Hardy Controller, you can take full advantage of WAVERSAVER®, and C2 Electronic Calibration.

### ANALOG SCALE (HI SBA Series)

Use the Analog output scale to provide 4-20mA output directly proportional to the weight reading. This version offers a low-cost, effective solution for bringing an analog weight reading directly into a

control system, with minimal additional wiring or hardware, and comes with a 15-foot two-wire shielded cable. The scale comes pre-calibrated from the factory but provides potentiometers for coarse and fine zero adjustment as well as span.

### DEVICENET SCALE (HI SBD Series)

With its built-in DeviceNet interface you can use this scale to provide a weight output to any point on a DeviceNet Network. This version also incorporates both the WAVERSAVER and C2 technologies, and comes with a six-inch pig-tailed connector.

Just set an address, connect to your network, configure and you're up and running. The scale features outputs for Gross, Net and Tare weight values and inputs for Zero and Tare commands. A Command interface provides easy access to all parameters without the need for explicit messages.

Need to recalibrate? One push of "THE BUTTON" automatically recalibrates the scale. The scale also supports C2 electronic calibration over its DeviceNet interface. WAVERSAVER eliminates the effects of vibration on the scale resulting in a clean accurate weight signal being transmitted over DeviceNet. The scale provides 20-bit resolution with a selectable conversion rate choice of 10 or 55 updates per second.

## Use ANY-WEIGH Bench Scales for:

- Filling & Dispensing
- IBC Dispensing
- Batching/Blending
- Check Weighing
- Flow Rate Monitoring
- Flow Rate Control
- Force Measurement
- Level Measurement/Control

## Weighing Instruments Dedicated to Your Applications

Controllers, Weight Modules, Transmitters

Allen-Bradley® Compatible Plug-in Weigh Scale Modules



HI 3000 & HI 4000  
Controllers and  
HI 6000 Series Weight  
Processors

## Hardy Load Cells

Hardy carries a wide variety of Load Cells to accommodate your application requirements.

ADVANTAGE Series  
with C2 Calibration



## SPECIFICATIONS

### Universal Scale (SBU)

#### Rated Output

- 0.900 ± 0.0009mV/V

#### Combined Error

- 0.030 %R.O.

#### Creep @ 30 min

- 0.030 %R.O.

#### Zero Balance

- 5.0 % R.O.

#### Temp Effect Output

- 0.0015% R.O./ °F

#### TempEffect Sensitivity

- 0.0008 % R.O./ °F

#### Comp.Temp. Range

- -10 - +40°C

#### Oper. Temp. Range

- -10 - +65°C

#### Input Resistance

- 297.5 ± 10% ohm

#### Output Resistance

- 250 ± 5% ohm

#### Excitation

- 5-15 Volts

#### Safe Load Limit

- 300 % Emax
- Ultimate Load 400% Emax

#### Max. Cornering Error

- 0.06% 1/2 full scale load, 1/2 way to corner

#### Warranty

- Two year warranty against defects in workmanship

### DeviceNet Out (SBD)

#### Resolution

- 20 bit

#### Update Rate

- 10 or 55 per second depending on WAVERSAVER settings

#### Averages

- 0-255 selectable

#### Temp Coefficient

- < 0.0023%/C

#### Input Power

- 11-25VDC

#### Type

- Generic

#### I/O Slave Message

- Polling

#### Baud Rates

- 125K, 250K, 500K

#### Inputs

- Gross, Net, Tare

#### Outputs

- Weight: Metric/Engl., Zero & Tare
- WAVERSAVER
- Calib . Type
- Span Weight (Hard Cal)
- Cal Low Value
- Cal High Value
- # of Averages

#### Warranty

- Two year warranty against defects in workmanship

### Analog Out (SBA)

#### Loop Power

- 15-50VDC across scale.
- A 15V min. would be with 0 ohm load; add 20mV/ohm to the min. loop voltage.
- A 500 ohm load would require 25V min. loop voltage.

#### Linearity

- 0.11% of full scale

#### Response Time

- 250 milliseconds

#### Temp. Range

- 0 to 60°C

#### Temp. Coefficient

- 0.025%/°C

#### Warranty

- Two year warranty against defects in workmanship

All specifications subject to change without notice. Please contact the Hardy factory or visit our website for the latest specifications.

## ORDERING INFORMATION

MODEL #	SIZE	CAPACITY	HEIGHT	WEIGHT
	in/mm	lb/kg	in/mm	lb/kg
HI 1212SB__-33	12" x 12" / 298 x 298	33/15	1.54/39.1	14/6.4
HI 1212SB__-66	12" x 12" / 298 x 298	66/30	1.56/39.6	14/6.4
HI 1212SB__-130	12" x 12" / 298 x 298	130/60	1.62/41.2	14/6.4
HI 2424SB__-130	24" x 24" / 600 x 600	130/60	1.62/41.2	52/23.6
HI 2424SB__-330	24" x 24" / 600 x 600	330/150	1.65/41.9	52/23.6
HI 2424SB__-660	24" x 24" / 600 x 600	660/300	1.87/47.5	52/23.6
HI 2424SB__-1.3K	24" x 24" / 600 x 600	1300/590	2.05/52.1	52/23.6

SBU: Universal    SBD: DeviceNet    SBA: Analog

## Hardy Process Solutions

10075 Mesa Rim Road  
San Diego, CA 92121  
tel. +1-858-278-2900  
tel. 800-821-5831  
fax +1-858-278-6700  
www.hardysolutions.com  
hardyinfo@hardysolutions.com

All information within is subject to change without notice. Visit our website for latest specifications. WAVERSAVER, C2, IT, ADVANTAGE and ANY-WEIGH are registered trademarks of Hardy Process Solutions, Inc.. Allen-Bradley and End-compass are trademarks of Rockwell Automation, Inc. All other trademarks or registered trademarks are the property of their respective owners.

